(21) Application No. 22456/78

(22) Filed 25 May 1978

(44) Complete Specification published 10 Dec. 1980

(51) INT. CL.3 G05D 3/00 G02B 27/00

(52) Index at acceptance G3N 275 381 E2X G5G 500Y 7

(72) Inventor KEITH CHRISTOPHER HOBBS



(54) IMPROVEMENTS IN OR RELATING TO CONTROL **DEVICES**

We, STANDARD TELEPHONES AND CABLES LIMITED, a British Company of 190 Strand, London W.C.2., England, do hereby declare the invention, for which we pray 5 that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:

This invention relates to a man/machine 10 interface, especially suitable for use by a disabled person, which uses optical coup-

ling to the human eye.

According to the present invention there is provided an electro-optical man-machine 15 interface arrangement, which includes a television camera aimed at an operator's eye such as to produce an image of that, an eye recognition circuit which identifies the eye on the image and so controls the 20 zoom circuitry of the camera as to get a large image of the eye, a shape analyser which examines the image and assesses from the shape of the iris of the eye as presented on the image the direction in 25 which the operator is looking, and means responsive to the determination of the direction in which the operator is looking to control a control element of the machine with which the arrangement is to be used. The human eye is a relatively simple

geometric structure, consistent in shape, size and colour contrast. Even when partly obscured by an eyelid it is possible to determine the direction in which the eye is 35 looking by analysis of the shape of the visible iris. When viewed directly along the line of sight the iris is circular. When viewed from other angles the iris icis is viewed from other angles the iris is elliptical, the major and minor axes being 40 dependent on the direction of vision and

viewing angle.

A human being can determine the direction in which another human is looking by analysis of this simple shape. This is 45 possible with some accuracy even when the

two persons are considerable distances apart. Television cameras are available with considerably better resolution than that of the human eye, and by analysing the picture produced by a T.V. camera it is 50 possible to determine electronically the precise line of sight of the observed eye.

An embodiment of the invention will now be described with reference to the accompanying drawing, the upper part of 55 which is a block diagram of a system embodying the invention, while the other

part is explanatory.

In Fig. 1, it will be seen that a TV camera 1 is aimed at the operator's eye 2, 60 and the analysis of the T.V. image of the

eye is performed in two stages:

1) By an eye recognition circuit 2 is fed from the camera 3 via a scanner 4, and which identifies the eyeball. It also con- 65 trols the zoom facility via the connection 5 on the camera so that the image of the

of sight of the eyeball.

If this information is used to determine the X-Y coordinates of an X-Y plotter 7. or alternatively the position of a dot on a T.V. screen, the operator can cause writing 75 on the screen by movement of the eye, precise control being achieved due to the feedback-loop as shown.

If the output of the analysed information is used to inform a keyboard or typeface 80 of the character being observed then character selection may be made optically. then

If the output of the analysed information is used to produce mechanical movement then an optically coupled remote control is 85 achieved.

WHAT WE CLAIM IS:-

1. An electro-optical man-machine interface arrangement, which includes a television camera aimed at an operator's eye such as 90

eye fills the picture. 2) The eyeball is now examined by the iris shape analyser 6 to determine the line 70 to produce an image of that eye, an eye recognition circuit which identifies the eye on the image and so controls the zoom circuitry of the camera as to get a large 5 image of the eye, a shape analyser which examines the image and assesses from the shape of the iris of the eye as presented on the image the direction in which the operator is looking, and means responsive 10 to the determination of the direction in

which the operator is looking to control a control element of the machine with which the arrangement is to be used

the arrangement is to be used.

2. An electro-optical man-machine interface arrangement, substantially as described 15 with reference to the accompanying draw-

S. R. CAPSEY, Chartered Patent Agent, For the Applicants.

Printed for Her Majesty's Stationery Office by The Tweeddale Press Ltd., Berwick-upon-Tweed, 1980. Published at the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.

1581018

COMPLETE SPECIFICATION

1 SHEET

This drawing is a reproduction of the Original on a reduced scale

